

ICOM

MF/HF MARINE TRANSCEIVER

IC-M710



Simple, dependable worldwide communications at an affordable price.

1136 channels

160 user-programmable, 242 ITU SSB duplex, 72 ITU SSB simplex and 662 ITU FSK duplex channels are available.

Rugged construction

The highest quality components are used throughout. Constructed in a die-cast aluminum chassis with surface mount components, the IC-M710 is designed for long hours of operation in the harsh marine environment.

Alphanumeric readout

The large, easy-to-read display shows status at a glance. Seven characters can be programmed into each memory channel to conveniently display station names, ship names, etc.

150 W of output power

A full 150 W (PEP) of output power is available for reliable long distance communication. A large cooling fan, in combination with the aluminum chassis, allows continuous transmission at full output power—even during demanding RTTY (radio teletype) and NBDP (narrow band direct printing) operation.

Automatic tuning function

An automatic tuning function is available when using the IC-M710 in combination with the optional AT-130/E for quick and easy antenna tuning. Tuning is fully automatic. When you push the PTT on a new frequency, the antenna tuner quickly tunes the antenna automatically.

Easy to use

Two large memory and frequency dials allow quick and easy operation.

GMDSS versions available

Versions which comply with GMDSS requirements are available. With the addition of an IC-GM110 DSC terminal the radio meets DSC class A requirements.

And more...

- Covers all allowed bands between 1.6 and 27.5 MHz
- General coverage receiver
- Modes: SSB, RTTY, CW and AM
- 2182 kHz alarm built-in (optional for General versions)
- RF gain control
- Audio activated squelch
- Terminals for frequency/mode control via NMEA interfacing
- Direct keypad channel selection entry
- Large, front-mounted speaker
- Weather fax ready
- Backlight control
- CW full break-in and semi break-in

Icom Inc.

SPECIFICATIONS

GENERAL

- Frequency coverage : Receive 500 kHz–29.999 MHz
Transmit* 1.6–27.5 MHz
*Restrictions may apply depending on version.
- Mode : J3E (USB), H3E, J2B (AFSK), F1B (FSK), R3E, A1A (CW)
(available modes may differ depending on version)
- Number of channels : 1136 (max.)
(160 user-programmable; 242 ITU SSB duplex; 72 ITU SSB simplex; 662 ITU FSK duplex)
- Antenna impedance : 50 Ω (nominal)
- Useable temperature range : -30 to +60°C (-22 to +140°F)
- Frequency stability : ± 10 Hz (-30 to +60°C; -22 to +140°F); ± 20 Hz above 15 MHz for General and Marine versions)
- Power supply requirement : 13.6 V DC $\pm 15\%$
(negative and floating grounds are available depending on version)
- Current drain (at 13.6 V DC) :

Transmit (max. output power)	30 A
Receive (max. audio output)	2.5 A (negative ground type)
	3 A (floating ground type)

- Dimensions : 291.4 (W) x 116.4 (H) x 315 (D) mm
(projections not included)
11¹³/₃₂ (W) x 4¹³/₃₂ (H) x 12¹³/₃₂ (D) in
- Weight : 7.9 kg; 17 lb 7 oz (negative ground type)
8.1 kg; 17 lb 14 oz (floating ground type)

TRANSMITTER

- Output power :
(U.S.A. versions) 150, 60, 20 W PEP (selectable)
(80, 20 W only for 25 MHz band)
(Europe versions) 150, 60, W PEP (selectable)
(60 W only for 25 MHz band)
- Spurious emissions : -65 dB (U.S.A. versions)
-60 dB (Europe versions)
- Carrier suppression : 40 dB
- Unwanted sideband suppression : 55 dB
- Microphone impedance : 600 Ω

RECEIVER

- Sensitivity :
J3E, R3E, J2B, F1B, A1A : 0.5 μ V (1.8–29.9999 MHz)
1 μ V (1.6–1.7999 MHz)
6.3 μ V (0.5–1.5999 MHz)
H3E : 3.2 μ V (1.8–29.9999 MHz)
6.3 μ V (1.6–1.7999 MHz)
32 μ V (0.5–1.5999 MHz)
(10 dB S/N)
- Spurious rejection ratio : 70 dB (1.6–29.9999 MHz)
- Audio output power : 4.5 W at 10% distortion with a 4 Ω load
- Audio impedance : 4 to 8 Ω
- Clarity variable range : ± 150 Hz

All stated specifications are subject to change without notice or obligation.

OPTIONS

GM-110DSC DSC TERMINAL UNIT



6 channel emergency scanning receiver —contains remote control capability of the IC-M710 GMDSS for distress calls, etc.

AT-130/E HF AUTOMATIC ANTENNA TUNER



Matches the transceiver to a long wire antenna with little insertion loss.

MN-100/MN-100L ANTENNA MATCHERS



Match the transceiver to a long wire antenna without applying DC power.

HS-50 HANDSET




Provides clear audio reception and comes in handy for listening privacy.

PS-60 DC POWER SUPPLY



Provides 13.6 V DC (30 A) output from an AC outlet.

PS-66 DC-DC CONVERTER



Provides 13.6 V DC (30 A) output from 19–32 V DC.

FL-100 CW/FSK NARROW FILTER (500 Hz–6 dB)



Have good shape factor to provide better CW/RTTY reception. A 350 Hz–6 dB NARROW FILTER is already built-in to the GMDSS versions.

UT-95 2-TONE ALARM UNIT



Already built-in to the Marine and GMDSS versions.

Les spécifications et informations données dans ce document peuvent être modifiées sans préavis.

ICOM FRANCE

Zac de la Plaine - 1, Rue Brindejonc des Moulinais
BP 5804 - 31505 TOULOUSE CEDEX
Tél : 05 61 36 03 03 - Fax : 05 61 36 03 00
WEB ICOM : <http://www.icom-france.com>
E-mail : icom@icom-france.com



Agence Côte d'Azur

Port Inland locaux N°112 et 113
701 avenue de Fontmichel - 06210 MANDELIEU
Tél : 04 92 19 68 00 - Fax : 04 92 19 68 01

CACHET REVendeur